



SURFACING DEPTH TABLE	CSBC	CSTC	HMA
RURAL	9"	3"	3"
URBAN LOCAL ACCESS	-	6"	2"

NOTES:

- 1) DITCH BOTTOMS TO HAVE BALLAST COMP. IN PLACE, 3" MIN. DEPTH IF ROAD GRADE IS 5% OR STEEPER.
- 2) THE NEED FOR CORRUGATED METAL PIPE, SIZE, & LOCATION TO BE DETERMINED BY THE COUNTY ENGINEER.
- 3) NEAT VERTICAL SAW CUT & TACK EDGES OF EXISTING PAVEMENT.
- 4) APPROACH SHALL BE PAVED TO THE RIGHT OF WAY LINE.
- 5) DEPENDING ON THE SITUATION THE DIMENSIONS SHOWN HEREON MAY BE VARIED AS REQUIRED BY THE COUNTY ENGINEER.

MINIMUM PAVED AREA

VARIES

EDGE OF PAVEMENT

VARIES (SEE NOTE # 4)

RADIUS MINUS 5'

RADIUS 35' MIN

RIGHT OF WAY

28'



PRIVATE ROAD APPROACH

APPROVED BY:

Matt M
 COUNTY ENGINEER

4/25/17
 DATE

STANDARD PLAN

R-4

SHEET 1 OF 1